



### Main Features:

- Tubular design
- Galvanised strand with soft eyes and alloy ferrules
- Used for general hauling applications



### Specifications:

| Bullivants Mfr No. | Size mm<br>(Outside Diameter) | Grip Length<br>mm | Ultimate Tensile<br>Strength kN |
|--------------------|-------------------------------|-------------------|---------------------------------|
| WCPS-010-014-C1-NC | 10 - 14                       | 350               | 5                               |
| WCPS-014-019-C1-NC | 14 - 19                       | 400               | 9                               |
| WCPS-019-028-C1-NC | 19 - 28                       | 500               | 15                              |
| WCPS-028-040-C1-NC | 28 - 40                       | 600               | 24                              |
| WCPS-040-055-C1-NC | 40 - 55                       | 800               | 35                              |
| WCPS-055-075-C1-NC | 55 - 75                       | 900               | 62                              |
| WCPS-075-095-C1-NC | 75 - 95                       | 1000              | 98                              |
| WCPS-095-120-C1-NC | 95 - 120                      | 1200              | 133                             |
| WCPS-120-150-C1-NC | 120 - 150                     | 1400              | 187                             |
| WCPS-150-190-C1-NC | 150 - 190                     | 1600              | 283                             |

Available with Copper Ferrules on request.

Available in Stainless Steel Strand variation on request.

Available in soft or thimble eye variations.w