

Bullivants

Geared Trolley

500kg – 10 Tonne



Main Features:

- Lightweight and high strength
- Wide Adjustment Range to suit most common beam sizes
- Extra wide 10 tonne unit available
- Low profile design
- Stainless Steel ID plates and rivets suitable for underground mining applications
- Standard hand chain length – 2.5m



ZERO HARM Product Features:

- Designed and tested in accordance with the AS1418.2
- Unique serial number and test certificate supplied with each item
- Comprehensive instruction manual supplied with each unit

Bullivants Mfr No.	Rated Capacity t	Beam Range mm	Unit Weight kg
WGT-0050-068-203-BV	0.5	68 – 203	7.4
WGT-0100-068-203-BV	1.0	68 – 203	12.0
WGT-0200-088-203-BV	2.0	88 – 203	18.0
WGT-0300-110-203-BV	3.0	110 – 203	30.0
WGT-0500-116-203-BV	5.0	116 – 203	47.0
WGT-1000-130-203-BV	10.0	130 – 203	79.0
WGT-1000-200-305-BV	10.0	200 – 305	86.0

Bullivants

Geared Trolley

500kg – 10 Tonne



Wide Beam Extension Kits*

Bullivants Mfr No.	Rated Capacity t	Beam Range mm
WETP-BVG-TK-0050	0.5	68 – 305
WETP-BVG-TK-0100	1.0	68 – 305
WETP-BVG-TK-0200	2.0	88 – 305
WETP-BVG-TK-0300	3.0	110 – 305
WETP-BVG-TK-0500	5.0	116 – 305

*Sold separately

Hand Chain:

Bullivants Mfr No.	Description	Suits
WHC-050ZS	Zinc Plated 5mm x 23.7mm Hand Chain	All Blocks
WCON-A-05-25-TG	Corrosion Resistant Hand Chain Joiner	All Blocks

Technical Data:

Capacity		0.5t		1t		2t		3t		5t		10t
Beam Width		68-203	68-305	68-203	68-305	88-203	88-305	110-203	110-305	116-203	116-305	130-203
	A	336.5	438.5	356.5	458.5	372.5	474.5	387.5	489.5	405.5	507.5	432
	B	212		248		293		350		382		471
	C	184		223.5		267.5		322		372		483
	D	22		28		34		42		46		72
	E	29.5		30		30		34.5		36.5		40
	F	3		3		3		3		5		5
Headroom	G	102.5		123		147		173.5		200		273
Min Curve Radius		0.6m		0.8m		1.0m		1.4m		1.0m		1.2m
All Dimensions in mm unless otherwise noted												

Technical Drawings:

