



Cradle Lift

- Come in two types:
 - Machine made woven flat cables (1A, 1B and 1C)
 - Handmade (1E and 1G)

1A

- U termination on both ends
- Slimmest woven steel sling
- Slides easily under load

1B

- U termination on one end and lapped eye with Ferrules on other end
- End with Ferrules remains on crane hook during rigging

1C


- Lapped eye with ferrule on both ends
- Lowest cost sling where clearances under loads are adequate

1E

- U Termination one end and hand formed soft eye on other end
- Very thin sling useful where clearance between bundles is limited

1G

- Lapped eye with ferrules one end and hand formed soft eye on the other



Specifications:

Bullivants Mfr No.	Nominal Dia. mm	Length	Single Fall WLL kN (Safety Factor 5:1)
WFWS-T1A-050-0200	50	2	10.2
WFWS-T1A-064-0600	64	6	16.0
WFWS-T1A-076-0400	76	4	23.8
WFWS-T1A-088-0600	88	6	31.6
WFWS-T1A-100-0400	100	4	42.5
WFWS-T1B-064-0400	64	4	16.0
WFWS-T1B-076-0400	76	4	23.8
WFWS-T1B-088-0400	88	4	31.6
WFWS-T1B-100-0400	100	4	42.5
WFWS-T1C-050-0300	50	3	9.0
WFWS-T1C-064-0500	64	5	16.0
WFWS-T1C-076-0250	76	2.5	23.8
WFWS-T1C-088-0250	88	2.5	31.6
WFWS-T1C-100-0300	100	3	42.5
WFWS-T1C-160-0800	160	8	100.0
WFWS-T1E-050-0250	50	2.5	9.0
WFWS-T1E-064-0250	64	2.5	16.0
WFWS-T1E-076-0300	76	3	23.8
WFWS-T1G-064-0200	64	2	16.0
WFWS-T1G-088-0200	88	2	31.6
WFWS-T1G-100-0300	100	3	42.5
WFWS-T1G-160-0600	160	6	100.0
WFWS-T1G-200-1000	200	10	150.0

Other sizes available up to 250mm nominal width
Protective covering available on request