

Bullivants

Girder Clamp

1 Tonne – 10 Tonne



Main Features:

- Low profile design to maximise headroom
- Wide Adjustment Range to suit most common beam sizes
- Lightweight and high strength
- Stainless Steel ID plates and rivets suitable for underground mining applications

ZERO HARM Product Features:

- Lightweight design to minimise risk of injury during overhead installation
- Unique serial number and test certificate with each unit
- Comprehensive instruction manual supplied with each unit
- Designed and tested to comply with the requirements AS4991



Specifications:

Bullivants Mfr No.	Rated Capacity t	Beam Range mm	Unit Weight kg
WGC-0100-075-220-BV	1.0	75 – 220	3.8
WGC-0200-075-220-BV	2.0	75 – 220	4.6
WGC-0300-080-320-BV	3.0	80 – 320	9.0
WGC-0500-080-320-BV	5.0	80 – 320	11.0
WGC-1000-090-320-BV	10.0	90 – 320	16.0

Bullivants

Girder Clamp

1 Tonne – 10 Tonne



Dimensions:

Bullivants Mfr No.	Safe Working Limit kg	Beam Width mm	A Max mm	B		C mm	D mm	E mm	F		G mm	H mm
				Min mm	Max mm				Min mm	Max mm		
WGC-0100-075-220-BV	1000	75-220	260	180	360	64	5	215	102	155	25	22
WGC-0200-075-220-BV	2000	75-220	260	180	360	74	6	215	102	155	25	22
WGC-0300-080-320-BV	3000	80-320	354	235	490	103	8	260	140	225	45	24
WGC-0500-080-320-BV	5000	80-320	354	235	490	110	10	260	140	225	45	28
WGC-1000-090-320-BV	10000	90-320	365	320	505	120	12	280	170	235	50	40

Technical Drawings:

