



Main Features:

- Extremely resistant to corrosion where salt water, acid or alkaline solutions are factors
- Not suitable for lifting applications



Regular Link

Bullivants Mfr No.	Grade	S mm Chain Size	Tolerance	R mm	Tolerance	F mm	Tolerance
WCSR-0406	316	4	±0.08	19	±0.3	15	±0.3
WCSR-0604	304	6	±0.10	27	±0.5	22.5	±0.4
WCSR-0606	316	6	±0.10	27	±0.5	22.5	±0.4
WCSR-0804	304	8	±0.10	32	±0.6	30	±0.5
WCSR-0806	316	8	±0.10	32	±0.6	30	±0.5
WCSR-1004	304	10	±0.10	41	±0.7	38	±0.7
WCSR-1006	316	10	±0.10	41	±0.7	38	±0.7

Short Link – Grade 316

Bullivants Mfr No.	S mm Chain Size	Tolerance	R mm	Tolerance		F mm	Tolerance	
WCSS-0606	6	±0.10	18.5	0.4	-0.2	20	±0.4	
WCSS-0806	8	±0.10	24	0.4	-0.2	26	0.6	-0.4
WCSS-1004	10	±0.10	28	0.4	-0.3	34	±0.7	
WCSS-1006	10	±0.10	28	0.4	-0.3	34	±0.7	

