

Bullivants

Aluminium & Copper Ferrules



Aluminium Ferrules

Features:

- Used in both steel and fibre core wire rope
- Made of seamless aluminium
- Ideal for machine splicing
- Complies with DIN 3093



Specifications:

Bullivants MFR No.	size mm	Weight kg
WFEA-015-D-S	1.5	0.001
WFEA-020-D-S	2.0	0.001
WFEA-025-D-S	2.5	0.001
WFEA-030-D-S	3.0	0.001
WFEA-035-D-S	3.5	0.001
WFEA-040-D-S	4.0	0.002
WFEA-050-D-S	5.0	0.003
WFEA-060-D-S	6.0	0.006
WFEA-080-D-S	8.0	0.012
WFEA-100-D-S	10.0	0.023
WFEA-120-D-S	12.0	0.052
WFEA-130-D-S	13.0	0.052
WFEA-140-D-S	14.0	0.097
WFEA-160-D-S	16.0	0.097

*Others sizes available on request.

Bullivants MFR No.	size mm	Weight kg
WFEA-180-D-S	18.0	0.142
WFEA-200-D-S	20.0	0.186
WFEA-220-D-S	22.0	0.246
WFEA-240-D-S	24.0	0.318
WFEA-260-D-S	26.0	0.480
WFEA-300-D-S	30.0	0.622
WFEA-400-D-S	40.0	1.750
WFEA-420-D-S	42.0	2.000
WFEA-520-D-S	52.0	3.800
WFEA-600-D-S	60.0	5.800
WFEA-660-D-S	66.0	7.870
WFEA-680-D-S	68.0	8.500
WFEA-740-D-S	74.0	8.500
WFEA-780-D-S	78.0	8.500

Copper Ferrules

Features:

- Made with seamless copper
- Ideal for machine splicing
- Complies with DIN 3093



Specifications:

Bullivants MFR No.	size mm	Weight kg
WFEC-015-D-S	1.5	0.001
WFEC-020-D-S	2.0	0.001
WFEC-030-D-S	3.0	0.002
WFEC-040-D-S	4.0	0.006
WFEC-050-D-S	5.0	0.011
WFEC-060-D-S	6.0	0.011

*Others sizes available on request.

Bullivants MFR No.	size mm	Weight kg
WFEC-080-D-S	8.0	0.047
WFEC-100-D-S	10.0	0.088
WFEC-120-D-S	12.0	0.153
WFEC-140-D-S	14.0	0.240
WFEC-160-D-S	16.0	0.400
WFEC-180-D-S	18.0	0.537