



Main Features:

- Heavy duty polyester outer casing for extra resistance to damage
- Each sling supplied with test certificate
- Suitable for recovery and towing operations
- Not to be used for lifting applications



Specifications:

Bullivants Mfr No.	Minimum Break Strength t	Length m
WRS-005-030-E-P	3.5	3.0
WRS-010-030-E-P	7	3.0
WRS-020-020-E-P	14	2.0
WRS-020-030-E-P	14	3.0
WRS-020-060-E-P	14	6.0
WRS-050-100-E-P	35	10.0
WRS-050-200-E-P	35	20.0
WRS-080-005-E-P	56	0.5
WRS-080-010-E-P	56	1.0
WRS-100-005-E-P	70	0.5
WRS-100-006-E-P	70	0.6
WRS-100-0085-E-P	70	0.85
WRS-100-010-E-P	70	1.0
WRS-100-020-E-P	70	2.0
WRS-100-030-E-P	70	3.0
WRS-100-040-E-P	70	4.0
WRS-100-060-E-P	70	6.0
WRS-100-100-E-P	70	10.0
WRS-200-015-E-P	140	1.5
WRS-200-020-E-P	140	2.0
WRS-200-025-E-P	140	2.5
WRS-200-030-E-P	140	3.0
WRS-200-040-E-P	140	4.0
WRS-200-050-E-P	140	5.0
WRS-200-060-E-P	140	6.0