

Bullivants


Powerform 35 1960 Grade



Powerform 35 1960 Tensile Grade is a flexible non-rotating rope with compacted strands.

Main Features:

- Construction 35xK7(16xK7:6x K7+6xK7-6xK7-1x7)
- Flexible steel wire rope
- High strength rope
- Maximum resistance to rotation
- Increased resistance to crushing
- Increased abrasion resistance resulting from the unique compaction process
- Suitable for use on single part and multi-part hoist receiving systems



Specifications:

Bullivants Mfr No.	Diameter mm	Approx. Weight kg/m	Minimum Breaking Load kN
W0130QIEB	13	0.850	155
W0140QIEB	14	0.986	180
W0160QIEB	16	1.290	233
W0180QIEB	18	1.630	300
W0190QIEB	19	1.820	331
W0200QIEB	20	2.010	372
W0210QIEB	21	2.220	402
W0220QIEB	22	2.430	444
W0240QIEB	24	2.900	531
W0260QIEB	26	3.400	621
W0280QIEB	28	3.940	720
W0320QIEB	32	5.150	944

Applications:

Mobile Crane:
Hoist Rope



Tower Crane:
Hoist Rope



Lattice Boom Crane:
Hoist Rope



Offshore Pedestal Crane:
Hoist Rope



Dock Side Crane:
Hoist Rope

