

Bullivants

Panther® Recovery Strop



Panther® recovery strops are lightweight, high-strength, low-stretch recovery towing strops designed to be reliable and safe for your mining and vehicle recovery operations. The 12-strand high strength core is made of Dyneema® SK78 fibre, and is covered with 100% Dyneema® HMPE chafe protection to provide the appearance and ease of handling a single leg tow sling with superior abrasion resistance. At a fraction of the weight of wire, chain or Kevlar®, Panther® radically reduces manpower requirements and safety hazards.

Main Features:

- Dyneema® SK78 / Dyneema® (Core / Cover) fibre
- Class II Core-Dependent Double Braid
- Abrasion resistant and durable Dyneema® fibre jacket
- Heavy duty and abrasion resistant DC Gard
- 100% UV stabilized with operating temperature range (-60 to 150°C)
- Floats and remains visible on water surfaces – will not sink in muddy conditions (specific gravity 0.92)
- Soft Eye allows greater flexibility and versatility



ZERO HARM Product Features:

- Low stretch (reduced recoil) minimising risk of injury
- Lightweight for fast change out reducing the risk of potential manual handling injuries
- Pink colour for high visibility



1300 LIFTING

info@bullivants.com
www.bullivants.com

Bullivants

Panther® Recovery Strop



Specifications:

Bullivants Mfr No.	Average Strength* (t)	Minimum Strength* (t)	Overall Length m	Unit Weight kg	Max Diameter mm	Nominal Eye Size mm
WSU1-040-200-0006-EE-DS	20	18	0.69	0.59	33	150
WSU1-040-200-030-EE-DS	20	18	3	1.63	27	300
WSU1-040-200-060-EE-DS	20	18	6	2.81	27	300
WSU1-040-200-100-EE-DS	20	18	10	4.4	27	300
WSU1-047-300-016-EE-DS	30	27	1.6	1.54	43	300
WSU1-047-300-060-EE-DS	30	27	6	3.67	35	300
WSU1-047-300-100-EE-DS	30	27	10	5.76	35	300
WSU1-058-550-0005-EE-DS	55	49	0.5	0.86	52	150
WSU1-058-550-0008-EE-DS	55	49	0.8	1.18	52	150
WSU1-058-550-010-EE-DS	55	49	1	1.36	52	300
WSU1-058-550-025-EE-DS	55	49	2.5	2.81	44	300
WSU1-058-550-060-EE-DS	55	49	6	5.85	44	300
WSU1-081-115-060-EE-DS	115	104	6	11.48	63	450
WSU1-081-115-100-EE-DS	115	104	10	18.01	63	450
WSU1-104-200-010-EE-DS	200	180	10	31.75	84	450
WSU1-104-200-015-EE-DS	200	180	15	45.81	84	450
WSU1-125-300-010-EE-DS	300	283	10	50.71	111	450
WSU1-125-300-015-EE-DS	300	283	15	73.03	111	450

*Panther lengths/strengths listed in the table above are standard product offerings.

Additional sizes available upon request.

Other lengths may require additional lead time. Contact your sales representative for stock availability



1300 LIFTING

info@bullivants.com

www.bullivants.com